

# KIOSK BAR-CODE PRINTER

Tiketing sistemi, parking karte, ...

## Thermal printer mechanism: **PM532B**

Cutter with long lifespan

Easy to integrate into kiosk designs

Printer module (3 inch thermal printer mechanism + auto cutter+ control board)

### TEHNIČKA SPECIFIKACIJA

Printing Method	Thermal
Printing Speed	220mm/second (max.)
Dots/line	40 dots/line
Resolution	8
Printing Width(mm)	72
Paper Width(mm)	80
Paper Thickness(μm)	56-150 μm
Feed Resolution(mm)	0.125
Dimension W x D x H(mm)	240x150x150
Weight(g)	1760
Head temperature detection	Thermostat
Paper detection	Transmission photo electricity switch
Black mark detection	Reflecting photo electricity pipe
Platen position detection	Light touch switch
Operation voltage (V)	24±10%
Logical voltage(V)	5±0.25
Form feeding motor voltage(V)	24±10%
Auto cutting motor voltage(V)	24±10%
Detection voltage (V)	5±0.25
Abrasion resistance	100 km
Auto cutting frequency	1 million times
Operating temperature(°C)	0 to 50 (no condensation)
Operating humidity(RH)	10% to 80% (no condensation)
Storage temperature(°C)	-25 to 70 (no condensation)
Storage humidity(RH)	5% to 95% (no condensation)

Easy Lording

Certificates

