

Beograd, Apr-17



KIOSK PRINTER – POS901

APPLICATIONS
TICKETING SYSTEMS
POS PRINTER

GENERAL

- Oil, water, dust proof
- High-quality thermal printer special design for kitchen condition
- Flexible installation on countertop or wall using optional bracket
- High printing speed of 180mm/s
- Optional kitchen buzzer alert



Specifications:

Printing Method	Thermal Line
Resolution	8dots/mm, 576dots/line
Effective Printing Width	72mm
Printing Speed	180mm/s
Character Set	ASCII, GB18030(Chinese), BIG5, Codepage
Self-defined Character	YES
Print Font	ANK: 12 x24 Chinese: 24x24
Barcode	1D: UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128, 2D: PDF417, QR CODE, DATAMATRIX
Graphic	Support bitmap downloading
Paper End Sensor	YES
Driver	Windows XP/Vista/7/8/8.1/10, Linux, OPOS
Interface	RS-232+USB+Ethernet
Cash drawer control	DC24V,1A, 6PIN RJ-11Socket
Power Supply (Adapter)	AC100 ~240V ± 10%(include) DC 24V, 2A
TPH	100KM
Auto Cutter	5,000,000 cuts
Paper Type	Thermal paper
Paper Width	79.5± 0.5mm
Paper Thickness	0.06 to 0.08mm
Paper Roll Diameter	Max. 80mm
Auto Cutter	Partial Cut
Operating Temp/Humidity	0-50°C/10%-80%
Storage Temp/Humidity	-20-60°C / 10%-90%
Dimension (LxWxH)	156x160x209mm