

PROIZVOD: POS902

Printer



Features:

- High speed printing 300mm/S
- Touch panel and front paper out
- Sound & Light alarm to remind take receipts
- Water Oil Dust proof design, better for kitchen

Specification:

Print	Printing Method	Thermal Line
	Printing Speed	300mm/s
	Resolution	8dots/mm, 576dots/line
	Effective Printing Width	72mm
Character	Character Set	ASCII, GB18030(Chinese),BIG5,Codepage
	Print Font	Codepage, ANK: 12 x24; 9x17; Chinese: 24 x 24
	Character per Line	42
Paper Spec	Paper Type	Thermal paper
	Paper Width	79.5± 0.5mm
	Paper Roll Diameter	Max: 80.0mm
	Roll Core Inner Diameter	13mm(min.)
	Paper Thickness	0.06~0.08mm
Ribbon Cassette		N/A
Paper Supply Method		Drop-in easy paper loading
	TPH	100km
Barcode		1D: UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128, 2D:PDF417,QR CODE, DATA matrix
Emulation		ESC/POS
Driver		Windows98/2000/NT/XP/Vista/Win7/Win8/Win10/Linux/OPOS
Sensor		Paper End Sensor
Drawer Port		1 Port
Interface		RS232 (DB9) +USB+Ethernet
Power Supply (Adapter)		AC100 ~240V ± 10%(include) DC 24V, 2A
Auto cutter	Type	Guillotine
	Life	500,000 cuts
	Cutting Method	Partial cut

©Copyright 2017. by ASPEKT System Integration d.o.o., Beograd, Srbija

ASPEKT System Integration d.o.o.

Požeška 67a, 11000 Beograd, Republika Srbija

+ 381 11 355 7599; +381 63 598 033

office@aspekt.rs