



Datum (Date): 08/06/2020



# QR SKENER & RFID ČITAČ

PART NO: RAD006 – NIŽE, U ORIGINALU



## PRODUCT PARAMETERS:

<b>2D Code Engine Component Parameters</b>	
Image Sensor	752X480
Light Source	White LED
Symbologies	2D: PDF417, QR CODE, DATA MATRIX, Support reading screen and printed code 1D: CODE 128, UCC/EAN-128, AIM-128, EAN-8 etc.
Reading Distance	10-55mm
Scan Angle	360° Full Angle
<b>Input and Output Parameters</b>	
Power Input	9-18VDC
Working Current	< 600mA
Can read like ISO14443A or ISO14443B card serial number	Such as second-generation ID card, FM1208 CPU card, M1 card (Mifare S50, Mifare S70 IC card), SRIX4K, etc.
Barcode or 2D code input	Wiegand 26/ 34 output, output IC card number (common read head function) and associated card number output in compliance with QR code reservation rules
Communication Interface	RJ45 10/100M TCP/IP, Extensible Wireless WIFI, Bluetooth
Communication Protocol	Support TCP / UDP / HTTP
Voice output	comes with voice, amplifier and speaker output, nearly 150 kinds of voice output, customizable voice
Device input	12V DC power input, 1 line gate input, 1 line exit button input, 1 line alarm input
Equipment output	2 way 250V/5A relay output, 1 way unlock, 1 way expansion can control door opener, light, water valve, etc.
Wiegand output	Wiegand 26/34 output
<b>Dimensions</b>	
Installation size	152mm * 85mm * 35mm (L*W*H), Compatible with standard 86 box