


PROFESIONALNA OPREMA ZA EVIDENCIJU I KONTROLU PRISTUPA - SERIJA: 5742

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>1 HASY-01B</p> <p>ACC. Kontroler PLAVA (HASY) SEIJA 1 x vrata; 2 x wiegand (26) periferije (RFID Čitača,...) - TCP/IP Kapacitet: ID 40,000; Rec. 100,000; anti-pass back; on-line ili off line režim rada - TCP/IP (10M/100) "self adaptive" Web Server; do max. 254 kontrolera - Dimenzije: : 160mm x 106mm; -40°C to 70°C; RH 10%-90%, "non-condensing"</p>	kom	125.00
	<p>2 HASY-02B</p> <p>ACC. Kontroler PLAVA (HASY) SEIJA 2 x vrata; 4 x wiegand (26) periferije (RFID Čitača,...) - TCP/IP Kapacitet: ID 40,000; Rec. 100,000; anti-pass back; on-line ili off line režim rada - TCP/IP (10M/100) "self adaptive" Web Server; do max. 254 kontrolera - Dimenzije: : 160mm x 106mm; -40°C to 70°C; RH 10%-90%, "non-condensing"</p>	kom	145.00
	<p>4 HASY-04B</p> <p>ACC. Kontroler PLAVA (HASY) SEIJA 4 x vrata; 4 x wiegand (26) periferije (RFID Čitača,...) - TCP/IP Kapacitet: ID 40,000; Rec. 100,000; anti-pass back; on-line ili off line režim rada - TCP/IP (10M/100) "self adaptive" Web Server; do max. 254 kontrolera - Dimenzije: : 160mm x 106mm; -40°C to 70°C; RH 10%-90%, "non-condensing"</p>	kom	195.00
	<p>11 HASY-R148-EM</p> <p>RFID ČITAČ KARTICA HASY-R148 125KHz WIEGAND 26/34 IP65 - Material : Plastic case; Size: 110*48*20mm; Communication Distance WG<100M - Built-in LED (Double Color LED) and and Buzzer</p>	kom	25.00
	<p>12 HASY-R148-MF</p> <p>RFID ČITAČ KARTICA HASY-R148 13.56MHz WIEGAND 26/34 IP65 - Material : Plastic case; Size: 110*48*20mm; Communication Distance WG<100M - Built-in LED (Double Color LED) and and Buzzer</p>	kom	30.00





PROFESIONALNA OPREMA ZA EVIDENCIJU I KONTROLU PRISTUPA - SERIJA: 5742

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>13 HASY-R148-EM-HID</p> <p>RFID ČITAČ KARTICA HASY-R148 125KHz & HID WIEGAND 26/34 IP65 - Material : Plastic case; Size: 110*48*20mm; Communication Distance WG<100M - Built-in LED (Double Color LED) and and Buzzer</p>	kom	35.00
	<p>14 HASY-R201-EM</p> <p>RFID ČITAČ KARTICA HASY-R201 125KHz WIEGAND 26 IP65 9~12VDC - Communication Distance WG≤100M; Dimension: L77.5mm x W42.8mm x H16.5mm</p>	kom	25.00
	<p>15 HASY-R201-MF</p> <p>RFID ČITAČ KARTICA HASY-R201 13.56MHz WIEGAND 26 IP65 9~12VDC - Communication Distance WG≤100M; Dimension: L77.5mm x W42.8mm x H16.5mm</p>	kom	30.00
	<p>16 HASY-R207</p> <p>RFID ČITAČ KARTICA HASY-R207 125KHz WIEGAND 26 IP65 9~12VDC - Communication Distance WG≤100M; Dimension: L75mm x W116mm x H16.8mm</p>	kom	30.00
	<p>17 HASY-R207-MF</p> <p>RFID ČITAČ KARTICA HASY-R207 13.56Hz WIEGAND 26/34 IP65 9~12VDC - Communication Distance WG≤100M; Dimension: L75mm x W116mm x H16.8mm</p>	kom	35.00
	<p>18 HSY-P120EM</p> <p>RFID Reader Wiegand; EM 125KHz IP68; Metal Case Size: 120*x56 x18mm </p>	kom	91.00

PROFESIONALNA OPREMA ZA EVIDENCIJU I KONTROLU PRISTUPA - SERIJA: 5742

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	19 HSY-P120M1 RFID Reader Wiegand; M1 13.56Mhz IP68; Metal Case Size: 120*x56 x18mm	kom	105.00
	20 HASY-R601 RFID ČITAČ KARTICA HASY DUAL FREQUENCY WIEGAND 26/34 9~15VDC - Dual frequency Card Reader; Acrylic panel, Plastic case; Size : 86*86*8.8mm - Frequency: 125Khz & 13.56Mhz; 13.56Mhz reader reject copy tag	kom	45.00
	21 HASY-S212H-EM-NW RFID ČITAČ KARTICA HASY-S212H-EM-NWP SAMOSTALAN & WIEGAND IN/OUT - Metal case, anti-vandal, digital backlit keypad, Silicone Keyboard; NON Waterproof - 2000 users, card (125KHz) or PIN code; Access way: card, pin, card+pin - Dim: 118x56x20mm; Temperature: -45°C~60°C	kom	35.00
	22 HASY-S212H-EM-WP RFID ČITAČ KARTICA HASY-S212H-EM-WP SAMOSTALAN & WIEGAND IN/OUT - Metal case, anti-vandal, digital backlit keypad, Silicone Keyboard; IP68 Waterproof - 2000 users, card (125KHz) or PIN code; Access way: card, pin, card+pin - Dim: 118x56x20mm; Temperature: -45°C~60°C	kom	40.00
	23 HASY-S212-EM RFID ČITAČ KARTICA HASY-S212-EM SAMOSTALAN & WIEGAND 26 METALNO KUĆIŠTE IP68 IP68 Waterproof standalone reader; 2000 users, card or PIN code Metal case, anti-vandal, digital backlit keypad, Metal Keyboard Three access way: card, pin, card + pin; Temperature: -45~60C°; Dim. 118 x 56 x 20mm	kom	45.00






PROFESIONALNA OPREMA ZA EVIDENCIJU I KONTROLU PRISTUPA - SERIJA: 5742

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>24 HASY-S212-MF</p> <p>RFID ČITAČ KARTICA HASY-S212-MF SAMOSTALAN & WIEGAND METALNO KUĆIŠTE IP68 IP68 Waterproof standalone reader; 2000 users, card or PIN code Metal case, anti-vandal, digital backlit keypad, Metal Keyboard Three access way: card, pin, card + pin WG26 input/output, with WG26 card reader function Ambient temperature: -45~60C°; Dimension : 118 x 56 x 20mm</p>	kom	55.00
	<p>25 HASY-ST02</p> <p>RFID ČITAČ KARTICA HASY-ST02-EM SAMOSTALAN & WIEGAND IN/OUT TOUCH TASTATURA Touch Keypad Standalone reader; Door Opening Time: 0-99s (Adjustable) 2000 users, card or PIN code; Accesses: card, pin, card + pin; Digital backlit touch keypad Temperature: -45 °C ~ 60 °C; Dimensions: 114 x 75 x 16mm</p>	kom	20.00
	<p>31 HASY-SF01</p> <p>SAMOSTALAN UREĐAJ ZA PREPOZNAVANJE GEOMETRIJE LICA & RFID ČITAČ KARTICA 1,000 Facial and 10,000 Card Users; Access ways: Facial or Cards WG26 input, for external reader; WG26 output, device can be used as a reader Door Open Time: 0~200s (Adjustable); Operating Temperature: -40°C~60°C; Working Voltage: DC12V; Size: 105*60*23mm</p>	kom	75.00
	<p>41 HASY-SF03</p> <p>DATA TERMINAL-PREPOZNAVANJE GEOMETRIJE LICA & RFID ČITAČ KARTICA - TCP/IP & USB - Dynamic Face Access Control; 4-inch IPS HD screen; Indoor/semi-outdoor; DC12V/2A - Face user capacity: 2000; Card user capacity: 2000; Logs record: 200,000 - NO/CN output, door opening button input, WG26/34 input and output, - Fire alarm input, door magnetic input, alarm output, RS485 input, and doorbell output - Dimensions: 165x85x22mm</p>	kom	125.00

PROFESIONALNA OPREMA ZA EVIDENCIJU I KONTROLU PRISTUPA - SERIJA: 5742

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>42 HASY-F301</p> <p>DATA TERMINAL-PREPOZNAVANJE GEOMETRIJE LICA & RFID ČITAČ KARTICA & TASTATURA</p> <ul style="list-style-type: none"> - TCP/IP & USB; Face Access Control and T & A - User:1000 Facial, 10000 Cards; Record Capacity: 160000; Fingerprint Verified Mode: 1:1; 1:N - Wireless Doorbell, Dual HD Dual camera; wiegand 26/34, tamper alarm, Reset function - FRR: ≤0.01%; FAR: ≤0.0001%; Verification Speed: ≤1s - Working Temperature: -10-45degree; Dimension: 172mm*89mm*31mm 	kom	175.00
	<p>43 HASY-F501</p> <p>DATA TERMINAL-PREPOZ. GEOMET. LICA & RFID ČITAČ KARTICA & TASTATURA & OTISAK</p> <ul style="list-style-type: none"> - TCP/IP & USB; Face Access Control and T & A - User:1000 Facial, 10000 Cards; Record Capacity: 160000; Fingerprint Verified Mode: 1:1; 1:N - Wireless Doorbell, Dual HD Dual camera; wiegand 26/34, tamper alarm, Reset function - FRR: ≤0.01%; FAR: ≤0.0001%; Verification Speed: ≤1s - Working Temperature: -10-45degree; Dimension: 172mm*89mm*31mm 	kom	225.00
	<p>51 HASY-F107E</p> <p>SKENER OTISKA PRSTA & RFID ČITAČ KARTICA & TASTATURA HASY WIEGAND</p> <ul style="list-style-type: none"> - Fingerprint & RFID Access Control; User capacity: Finger 1000, Card 1000, PIN 1000 - 3 access modes: fingerprint, card, PIN; Wiegand 26 bits output, with card reader function - Operating Voltage: DC12V; Dimensions: 88mm * 88mm * 30mm 	kom	35.00
	<p>71 HASY-315</p> <p>Seriya HASY RFID Čitač Kartica EM, ili Mifare "TOUCH" ŠIFRATOR STAND ALONE</p> <ul style="list-style-type: none"> - Display OLED; DC12V -10°C ~ 55°C Komunikacija: 1 x wiegan IN, 1 x wiegand out - 1000 Korisnika; Memorija za do 100,000 rekorda, "prenos" podataka pomoću USB-diska - Dimenzije: 117*78*22mm 	kom	65.00
	<p>81 HASY-U183-EM</p> <p>RFID ČITAČ KARTICA HASY USB - DESKTOP EM 125MHz; Dimension: 110x80x25mm</p>	kom	10.00


PROFESIONALNA OPREMA ZA EVIDENCIJU I KONTROLU PRISTUPA - SERIJA: 5742

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>82 HASY-U183-MF</p> <p>RFID ČITAČ KARTICA HASY USB - DESKTOP MF 13.56GHz; Dimension: 110x80x25mm</p>	kom	15.00
	<p>83 HAY-U183-MRW</p> <p>RFID ČITAČ / PISAČ KARTICA HASY USB - DESKTOP MF 13.56GHz; Dimension: 110x80x25mm</p>	kom	45.00
	<p>150 HASY-E60</p> <p>ELEKTRO BRAVA HASY TIP: "DROP BOLT LOCK"; UNIVERZALNA</p> <ul style="list-style-type: none"> - Surface Mounted Bolt Lock; Fail safe, Locked when energized - Lock Size: 150*34*28mm; Time Delay: 0/3/6sec; Door status Output,NO/COM - Suitable For: Narrow Door (Wooden/Metal or PVC Door) 	kom	35.00
	<p>151 HASY-E30B</p> <p>ELEKTRO BRAVICA HASY ZA STAKLENA VRATA</p> <ul style="list-style-type: none"> - Electric Bolt for Frameless Glass Door; Voltage: DC12V,Current: 900mA - Low Temperature, Locked when energized; Timer: 0 / 3 / 6 seconds available to set - Signal Output: Door Status Output,NO/COM; Size:148Lx43WX39/25H(mm)" 	kom	70.00
	<p>170 HAD01-PUSH</p> <p>MOTOR ZA (OTVARANJE/ZATVARANJE) KRILNA VRATA HASY HAD01-PUSH</p> <ul style="list-style-type: none"> - Automatic Swing Door Operator; 220 ~ 240VAC; -20°C~55°C - Opening time: 3~7s / 90°; Opening and holding time: 1-30s - Push arm installation: suitable for door swing opening outward 	kom	245.00

PROFESIONALNA OPREMA ZA EVIDENCIJU I KONTROLU PRISTUPA - SERIJA: 5742

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	171 HAD01-PULL MOTOR ZA (OTVARANJE/ZATVARANJE) KRILNA VRATA HASY HAD01-PULL - Automatic Swing Door Operator; 220 ~ 240VAC; -20°C~55°C - Opening time: 3~7s / 90°; Opening and holding time: 1-30s - Pull arm installation: suitable for door swing opening inward	kom	245.00
	200 HASY-08 ZAŠTITNI POKLOPAC HASY ZA RFID ČITAČE; PVC; ZAŠTITNA GUMA - Rain shield (rainproof housing); Dimension: Outside: 15cm* 10.4cm*9c - Inside: 13.5cm*8.9cm*8.4cm (L*W*Tlength is less than 13 cm)	kom	7.00
	301 AK6-B EXIT "TOUCH" TASTER - NAZIDNI; LED Indicator; Output contact: NO/NC/COM; 12VDC - Touch screen exit button; SPDT touch sensitive switch unit designed - Dimensions : 86Lx50Wx20H(mm); Mechanical life: 100,000 tests	kom	9.50
	302 ANT20 SENZOR "NO TOUCH"; Ø32/Ø28x25mm; 12VDC~24V Output contact: NO/NC/COM; with Blue/Green LED lights; Mechanical life: 100,000 tests	kom	10.00
	303 ANT32 SENZOR "NO TOUCH" WATERPROOF (IP68); Ø32/Ø28x25mm; 12VDC~24V Output contact: NO/NC/COM; with Blue/Green LED lights; Mechanical life: 100,000 tests	kom	15.00
	401 HASY-K11A DALJINSKE KOMANDE SERIJA HASY 1 x Rx (1Ch) + 1 x Tx (2Ch daljinac); 12VDC - Wireless Remote Control Switch; Working Frequency: 433Mhz - Transmitting Distance:50~150M; Output Mode: Switching Signal (Dry Contact) NO/NC	kom	35.00

PROFESIONALNA OPREMA ZA EVIDENCIJU I KONTROLU PRISTUPA - SERIJA: 5742

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	402 <input type="text"/> DALJINSKE KOMANDE SERIJA HASY 1 x Tx (2Ch daljinac) Wireless Remote Control; Working Frequency: 433Mhz; Transmitting Distance:50~150M	kom	10.00