





Profesionalna oprema: Acc. kontroleri i kompatibilne (wiegand) periferije
 - RFID, UHF, NFC, BarCode, Mag. Stripe, Otisak prsta, prepoznavanje geometrije lica, ...

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>1 AE01</p> <p>ACC. Kontroler za JEDNA vrata za DVE wiegand (26, 34, 37) periferije (RFID čitača,...) - TCP/IP Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za jedan Exit taster, za jedan senzor vrata; za jedan PP alarm - IZLAZI (relay): za jedna vrata; za jednu sirenu</p>	kom	145.00
	<p>2 AE02</p> <p>ACC. Kontroler za DVOJA vrata za ČETIRI wiegand (26, 34, 37) periferije (RFID čitača,...) - TCP/IP Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za dva Exit tastera, za dva senzora vrata; za dva PP alarma - IZLAZI (relay): za dvoja vrata; za dve sirene</p>	kom	195.00
	<p>4 AE04</p> <p>ACC. Kontroler za ČETVORA vrata za ČETIRI wiegand (26, 34, 37) periferije (RFID čitača,...) - TCP/IP Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za četiri Exit tastera, za četiri senzora vrata; za dva PP alarma - IZLAZI (relay): za četvora vrata; za dve sirene</p>	kom	225.00
	<p>5 AE04D</p> <p>ACC. Kontroler za ČETVORA vrata OSAM x wiegand (26, 34, 37) periferija (RFID čitača,...) - RS485 za OSAM periferija (RFID čitača, bar code skenera, itd) - TCP/IP Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za četiri Exit tastera, za četiri senzora vrata; za dva PP alarma - IZLAZI (relay): za četvora vrata; za dve sirene</p>	kom	275.00

Profesionalna oprema: Acc. kontroleri i kompatibilne (wiegand) periferije
 - RFID, UHF, NFC, BarCode, Mag. Stripe, Otisak prsta, prepoznavanje geometrije lica, ...

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>6 MAY104T</p> <p>LINUX ACC. Kontroler za ČETVORA VRATA OSAM PERIFERIJA (RFID ČITAČA, ILI ...) - PRERIFERIJE MAX. OSAM wiegand (26, 34, 37) PERIFERIJA (RFID čitača,...), ILI - PRERIFERIJE MAX. OSAM RS485 PERIFERIJA (RFID čitača, bar code skenera, itd) - TCP/IP Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za četiri Exit tastera, za četiri senzora vrata; za dva PP alarma - IZLAZI (relay): za četvora vrata; za dve sirene</p>	kom	295.00
	<p>7 AE05</p> <p>Acc. Kontroler Lift, Pretinci, ... 32 x Relay: 2xWiegand Citac; 32 x senzor vrata; 1 x PP alarm - Izlazi (relay): 32 x vrata; 2 x (PP Sirena&Svetlo) bez kutije i napajanja - TCP/IP - Web Server, opcija RS485 (do max. 254 Acc. Kontroler) - ID 120,000; Rec. 200,000</p>	kom	345.00
	<p>34 AR9EM</p> <p>MINI (TASTER Ø22/20mm) RFID Čitač Kartica Wiegand 26/34 - EM: 125KHz -25°C~70°C Working humidity 0%~99% Color: silver</p>	kom	25.00
	<p>35 AR9M1</p> <p>MINI (TASTER Ø22/20mm) RFID Čitač Kartica Wiegand 26/34 - MIFARE: 13.56MHz -25°C~70°C Working humidity 0%~99% Color: silver</p>	kom	35.00
	<p>37 AEM1000-125KHz</p> <p>RFID Čitač Kartica EM (125KHz) wiegand reading distance : 30 ~ 120mm - Max. rastojanje od Acc. Kontrolera < 150m -25°C ~ 70°C - Unutrasnja (spoljna natkrivena) primena LED (blue - green - LOGO can be customerized</p>	kom	30.00

Profesionalna oprema: Acc. kontroleri i kompatibilne (wiegand) periferije
- RFID, UHF, NFC, BarCode, Mag. Stripe, Otisak prsta, prepoznavanje geometrije lica, ...

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	38 AEM1000-13.56MHz	kom	35.00
	RFID Čitač Kartica M1 (13.56MHz) wiegand reading distance : 30 ~ 120mm - Max. rastojanje od Acc. Kontrolera < 150m -25°C ~ 70°C - Unutrasnja (spoljna natkrivena) primena LED (blue - green) - Logo: "ASPEKT" (po zahtevi možemo dodati i logo kupca, za kol. +50kom)		
	39 AHID-1000	kom	70.00
	RFID Čitač Kartica HID wiegand Reading HID card reading distance : 10--15CM - LED status: after powering, blue, and swipe card, change to Green - LOGO can be customized		
	40 RA-128	kom	55.00
	RFID Citac Kartica EM, ili M1 Wiegand 26, 34 rang: 3 ~ 12cm - rastojanje od Acc. < 150m -20°C ~ 55°C Spoljna primena buzzer - Metalno kuciste, vodo-otporno DC12V ~ 15V, bez napajanja		
	41 ADT5515	kom	65.00
	RFID Citac Kartica EM: 125KHz, opcije M1 13.56MHz, HID, NFC rang: 3 ~ 7cm - Wiegand 26/34, rastojanje od Acc. < 100m Opcija RS485/RS232, od Acc. < 1200m - IP65, -45°C ~ 70°C metal case; water proof; Shockproof; anti vandal - Namenjen za izrazito teške uslove rada		
	45 ACAM211B-EM	kom	55.00
	Seriya GB RFID Citac Kartica EM 125KHz Wiegand & STAND ALONE + ulaz za eksterni citac - Šifратор "touch metal keypad" rang: 3 ~ 12cm rastojanje od Acc. < 150m - Spoljna primena buzzer metalno kuciste, vodo-otporno - DC12V ~ 15V; ID Card, Users 2000 -20°C ~ 55°C		

Profesionalna oprema: Acc. kontroleri i kompatibilne (wiegand) periferije
- RFID, UHF, NFC, BarCode, Mag. Stripe, Otisak prsta, prepoznavanje geometrije lica, ...

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	46 AMA-1	kom	75.00
	RFID Citac Kartica EM, ili Mifare Wiegand & STAND ALONE + ulaz za eksterni citac - Šifратор "touch keypad" rang: 3 ~ 12cm rastojanje od Acc. < 150m -20°C ~ 55°C - Spoljna primena (natkriveno) buzzer metalno kuciste, vodo-otporno - DC12V ~ 15V; ID Card, Users 2000		
	48 U2	kom	75.00
	RFID Citac Kartica EM, ili Mifare Wiegand 26/34 input & output & STAND ALONE - METALNO KUĆISTE; vodo-otporno IP68; anti vandal LED, buzzer - Rang: 3 ~ 12cm rastojanje od Acc. < 150m -35°C ~ 60°C - DC12V; ID Card, Users 2000 Certification: RoHs, FCC, CE		
	50 DT5522ID	kom	125.00
	RFID Citac Kartica EM, ili M1 Tastatura & LCD Displej RS485 rang: 3 ~ 12cm - Rastojanje < 1,200m -20°C ~ 55°C Unutrasnja primena buzzer DC12V ~ 15V !		
	52 AF6-USB	kom	135.00
	Fingerprint Scanner RFID (EM) REader out door metal case; water proof; anti vandal - USB; RS232; RS485; wiegand 26, 34 stand alone Fingers 1000 ID Card 1000 - 2xFinger; 1xCard Card, ili FP Card + FP		
	55 AS600-EM	kom	70.00
	Citac Kartica EM (125MHz) Wiegand & STAND ALONE Šifратор "metal keypad" IP68 - rang: 3 ~ 12cm rastojanje od Acc. < 150m -45°C ~ 60°C Spoljna primena; buzzer - metalno kućiste, vodo-otporno; anti-vandal DC12V ~ 15V - U "stand alone" režimu kapacitet 2,000 (RFID Kartica, PWD različitih) - Na "wiegand"-u kapacitet 30,000 (RFID Kartica, PWD različitih)		


Profesionalna oprema: Acc. kontroleri i kompatibilne (wiegand) periferije
 - RFID, UHF, NFC, BarCode, Mag. Stripe, Otisak prsta, prepoznavanje geometrije lica, ...

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>56 AS600-MIFARE</p> <p>Citac Kartica MIFARE Wiegand & STAND ALONE Šifrator "metal keypad" IP68 - rang: 3 ~ 12cm rastojanje od Acc. < 150m -45°C ~ 60°C Spoljna primena; buzzer - metalno kućiste, vodo-otporno; anti-vandal DC12V ~ 15V - U "stand alone" režimu kapacitet 2,000 (RFID Kartica, PWD različitih) - Na "wiegand"-u kapacitet 30,000 (RFID Kartica, PWD različitih)</p>	kom	70.00
	<p>57 AHCC760-MSR</p> <p>Citac Kartica Mag. Stripe Wiegand26 "swipe" - kontakt - Rastojanje od Acc. < 100m -10°C ~ 70°C Metalno kuciste</p>	kom	125.00
	<p>70 HASY-315</p> <p>Seriya HASY RFID Čitač Kartica EM, ili Mifare "TOUCH" ŠIFRATOR STAND ALONE - Display OLED; DC12V -10°C ~ 55°C Komunikacija: 1 x wiegan IN, 1 x wiegand out - 1000 Korisnika; Memorija za do 100,000 rekorda, "prenos" podataka pomoću USB-diska - Dimenzije: 117*78*22mm</p>	kom	50.00
	<p>88 YAFBAK-8100</p> <p>SAMOSTALNI RFID ČITAČ-BLUETOOTH-"TOUCH" TASTATURA IP66 SERIJA 4000 - Opcije otključavanja: autorizovana ŠIFRA i/ili RFID Kartica i/ili korisnički mobilni telefon - Upravljanje sistemom: "master" mobilni telefon (ANDROID, IOS, Bluetooth 4.0) - Kapacitete: 20.000 RFID Kartica ŠIFRA i/ili Korisničkih mob. Telefona: ne ograničen</p>	kom	95.00
	<p>89 YAFBA-8100</p> <p>SAMOSTALNI RFID ČITAČ-BLUETOOTH-ZVONCE "TOUCH" TASTER IP66 SERIJA 4000 - Opcije otključavanja: autorizovana RFID Kartica i/ili korisnički mobilni telefon - Upravljanje sistemom: "master" mobilni telefon (ANDROID, IOS, Bluetooth 4.0) - Kapacitete: 20.000 RFID Kartica Korisničkih mob. Telefona: ne ograničen - Napajanje 12VDC; potrošnja 50mA; materijal: tamperisano staklo, aluminijumski okvir</p>	kom	90.00

Profesionalna oprema: Acc. kontroleri i kompatibilne (wiegand) periferije
- RFID, UHF, NFC, BarCode, Mag. Stripe, Otisak prsta, prepoznavanje geometrije lica, ...

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>91 AT-STU-8220</p> <p>AZT UHF Čitač sa MINI antenom, rang >3m RS232, RS485, wiegand 26/34 - 170 × 120 × 50 mm 902~928MHz, 865~868MHz -25°C~+95°C; 1.0kg DC 7.5V~12V, 3A - Support protocols: ISO18000-6B, EPC Class 1, EPC Class 1 GEN 2 SDK - RF power range: 0~30 dBm Identify tag mode: trigger, or auto - Frekvencije dozvoljene za javnu upotrebu u Evropi 868MHz</p>	kom	295.00
	<p>92 RF101</p> <p>UHF Citac dugog dometa 1 ~ 6m RS232, RS485, wiegand 26/34 EU slobodna za koriscenje frekvencija; protocal: ISO-18000-6B/6C DLL ugaona polarizacija </p>	kom	345.00
	<p>93 RF102</p> <p>UHF Citac dugog dometa > 15m RS232, RS485, wiegand 26/34 EU slobodna za koriscenje frekvencija; protocal: ISO-18000-6B/6C DLL Ugaona polarizacija </p>	kom	395.00
	<p>101 A805FaceRec</p> <p>Face Recognition camera 500 users USB; RS232; TCP/IP; web server wiegand (In/Out) - ID Card EM po visini 145 ~ 195cm rang: 30 ~ 80cm - 2G SD Card (Support up to 500,000 records) </p>	kom	345.00
	<p>102 ASC103/ASC403</p> <p>DATA TERMINAL RFID (125KHz) TA+ACC EVIDENCIJA I KONTROLA PRISTUPA - TCP/IP, USB host, RS232/485; 30,000 user; 50,000 records; anti-pass back; webserver - 50 x Time Zone, 5 x Grouping, 10 x Combination Wiegand In/Out - Audio Visual Indicator: Red LED (Access denied) / Green LED (Access granted) - With Audible Beep; Dim: 159*136*40mm; 0°C ~ 45°C; RH 20% ~ 80% - Opcije: Mifare, HID, - CE, FCC, RoHS Sertifikati</p>	kom	185.00






Profesionalna oprema: Acc. kontroleri i kompatibilne (wiegand) periferije
 - RFID, UHF, NFC, BarCode, Mag. Stripe, Otisak prsta, prepoznavanje geometrije lica, ...

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>103 ACAM103</p> <p>DATA TERMINAL RFID (13.56GHy) TA+ACC EVIDENCIJA I KONTROLA PRISTUPA - TCP/IP, USB host, RS232/485; 30,000 user; 50,000 records; anti-pass back; webserver - 50 x Time Zone, 5 x Grouping, 10 x Combination Wiegand In/Out - Audio Visual Indicator: Red LED (Access denied) / Green LED (Access granted) - With Audible Beep; Dim: 159*136*40mm; 0°C ~ 45°C; RH 20% ~ 80% - Opcije: Mifare, HID, - CE, FCC, RoHS Sertifikati</p>	kom	195.00
	<p>105 ASAI1201</p> <p>DATA TERMINAL DAHUA RFID Čitač Kartica Mifare "TOUCH" ŠIFRATOR ETHERNET RTC - 9~15VDC/200mA -30°C ~ 60°C IP 68 DTM to PC: TCP/IP - RJ45 (10/100M) - Comm In: 1 x Reader - wiegand / RS485 1 x Door sensor 1 x Exit tastar - Comm Out: 1 x Relay (Door lock) - ID 30,000; REC. (MEM) 150,000; Dimenzije:62*23*142mm; 0.5kg - Option: EM 125KHz ("D")</p>	kom	95.00
	<p>107 AE01-NET-B</p> <p>DATA TERMINAL AOP AOP RFID Čitač Kartica ETHERNET (TCP/IP) - ID Card holder: 21000, Logs 50,000 Alarm; 60,000 Events - External Card reader (1) IN on wiegand; EXIT button (1) IN; Fire alarm (1) IN - Door sensor (1) IN; Door lock NO/NC (1) OUT</p>	kom	90.00
	<p>108 AE01-NET-B-K</p> <p>DATA TERMINAL AOP RFID Čitač Kartica & TASTATURA & ZVONCE ETHERNET (TCP/IP) - ID Card holder: 21000, Logs 50,000 Alarm; 60,000 Events - External Card reader (1) IN on wiegand; EXIT button (1) IN; Fire alarm (1) IN - Door sensor (1) IN; Door lock NO/NC (1) OUT; Zvonce (1) NC OUT</p>	kom	95.00



Profesionalna oprema: Acc. kontroleri i kompatibilne (wiegand) periferije
- RFID, UHF, NFC, BarCode, Mag. Stripe, Otisak prsta, prepoznavanje geometrije lica, ...

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>109 AE01-NET-B-LCD</p> <p>DATA TERMINAL AOP RFID Čitač Kartica & TASTATURA & ZVONCE LCD ETHERNET (TCP/IP)</p> <ul style="list-style-type: none"> - ID Card holder: 21000, Logs 50,000 Alarm; 60,000 Events - External Card reader (1) IN on wiegand; EXIT button (1) IN; Fire alarm (1) IN - Door sensor (1) IN; Door lock NO/NC (1) OUT; Zvonce (1) NC OUT 	kom	100.00
	<p>111 ADT5512- USB</p> <p>Citac Kartica RFID EM: 125KHz USB rang: 3 ~ 15cm </p>	kom	33.00
	<p>112 ADT5512-USB -MF</p> <p>Citac Kartica RFID Mifare: 13.56KHz USB rang: 3 ~ 15cm </p>	kom	39.00
	<p>113 ADT5512-HID-R</p> <p>HID USB READER Interface: USB Read HID 26,34,35,36,37,40bits (125khz)</p>	kom	125.00
	<p>116 ADT5512-HID</p> <p>HID PROGRAMER Interface: USB Providing many interface functions Program</p> <ul style="list-style-type: none"> - HID 26,34,35,36,37,40bits compatible cards 	kom	750.00
	<p>117 AER300L</p> <p>NFC card issuer, send NFC UID card no. we can set card output no. format,</p> <ul style="list-style-type: none"> - working with NFC mobile phone. 	kom	95.00

Profesionalna oprema: Acc. kontroleri i kompatibilne (wiegand) periferije
- RFID, UHF, NFC, BarCode, Mag. Stripe, Otisak prsta, prepoznavanje geometrije lica, ...

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>118 AER302</p> <p>NFC card writer, can change Ultralight card to NFC card, provide SDK, and samples, - can identify different types of card, read and write NFC tags, - Elink make website linking automatically, - Eflow makes text input, Epurse can realize consumption, - and can save consumption records.also write person and things info. - can modify sector PSW, and initialize whole card.</p>	kom	125.00
	<p>119 AZT-STU-6212</p> <p>AZT UHF RFID Desktop Reader/writer USB effective distance up to 100cm - 120×78×25 mm 902~928MHz, 865~868MHz -20°C~+65°C - Tag protocols: ISO18000-6B,EPC Class 1,EPC Class 1 GEN 2; Software Development Kit - Communication interface: Double USB (1.USB to serial port, 2.USB to keyboard input)</p>	kom	225.00
	<p>131 APS26</p> <p>KONVERTER PS2 na Wiegand 26, 34 - PS2 to Wiegand 26bit or Wiegand 34bit</p>	kom	70.00
	<p>132 AWST-RS232WG</p> <p>KONVERTER RS232 na Wiegand 26, 34 - converter support double-way transmission; Wiegand 26bit or Wiegand 34bit to RS232 - RS232 to Wiegand 26bit or Wiegand 34bit</p>	kom	45.00
	<p>133 AWST-WG2USB</p> <p>KONVERTER USB na Wiegand 26, 34 - converter support double-way transmission; Wiegand 26bit or Wiegand 34bit to USB - USB to Wiegand 26bit or Wiegand 34bit</p>	kom	75.00

Profesionalna oprema: Acc. kontroleri i kompatibilne (wiegand) periferije
- RFID, UHF, NFC, BarCode, Mag. Stripe, Otisak prsta, prepoznavanje geometrije lica, ...

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	141 PD-132 Kontroler za induktivnu petlju AOP (DIN šina); 1Ch; 4 nivoa osetljivosti 230V / 5A - 4 frekventna opsega 3 rezima rada 2 relejna izlaza -20 ~ 65°C - Opcija: 24VDC CE, FCc i RoHS Sertifikati	kom	75.00
	142 PD-234 Kontroler za induktivnu petlju AOP (DIN šina); 2Ch; 4 nivoa osetljivosti 230V / 5A - 4 frekventna opsega 3 rezima rada 4 relejna izlaza -20 ~ 65°C - Opcija: 24VDC CE, FCc i RoHS Sertifikati	kom	125.00